



Pneumatic agitators

Complete range of pneumatic agitators designed for mixing fluids with maximum efficiency. Different configurations, motors and propellers for low, medium or high viscosity fluids. ATEX option upon request.





PNEUMATIC PAINT AGITATORS



Engine: Orion

- Recommended speed: 300 - 3000 rpm.
- Power: 3/4 HP (0.56 kW)
- Max. pressure: 7 bar.
- Capacity: 20-200 liters.
- Application: medium and high viscosity.



Engine: Pegasus

- Recommended speed: 300 - 3000 rpm.
- Power: 3/4 HP (0.56 kW)
- Max. pressure: 7 bar.
- Capacity: 20-200 liters.
- Application: medium and high viscosity.



Engine: Atom

- Recommended speed: 500-6000 rpm.
- Max. pressure: 7 bar.
- Power: 1/3 HP (0.25kw).
- Capacity: 20-40 liters.
- Application: low viscosity.



Engine: Aquarius

- Recommended speed: 500-6000 rpm.
- Max. pressure: 7 bar.
- Power: 1.4 HP (1.04 kW).
- Capacity: 20-200 liters.
- Application: high viscosity.



The Surface Finishing Expert



PRODUCT AND SERVICES

Portable blasting equipments / Nozzles and nozzle holders / Hoses and couplings / Lighting systems / Wet blasting / Dust-free Vacuumblast / Waterjetting / Abrasive vacuum recovery systems / Dust collectors / Dehumidifiers / Blast rooms / Blast cabinets / Internal pipe cleaners / Airless painting equipment / Plural component systems / Internal pipe painting / Low pressure painting equipments / Dry ice blasting / Personal protection / Measuring instruments / Abrasives

CONTACT

Couto Industrial
P.I. Mora Garay
C/ Marie Curie 47
32211 Gijón
Principado de Asturias / España

T. (+34) 985 30 84 65 /66
Fax: (+34) 985 32 46 30
info@coutoindustrial.com
www.coutoindustrial.com

